

# C25C

IC-CUSHION      LPG/DUAL FUEL  
 4000 / 5000 / 6000 / 6500 lbs.  
 (2000 / 2500 / 3000 / 3200 kg)

GEN2



## STANDARD SPECIFICATIONS

## C20/25/30/32C

Manufacturer's Designation		C20CL	C25CL	C30CL	C32CL
Load Capacity / Rated Load	lbs(kg)	4000 (2000)	5000 (2500)	6000 (3000)	6500 (3200)
Height Overhead Guard	in(mm)	82.8 (2105)	82.8 (2105)	82.8 (2105)	82.8 (2105)
Width	in(mm)	42.5 (1080)	42.5 (1080)	43.7 (1110)	45.4 (1154)
Right Angle Stack (add load length and clearance)	in(mm)	94.5 (2399)	96.8 (2459)	99.2 (2519)	101.4 (2575)
Outside Turning Radius	in(mm)	77.8 (1975)	134.6 (3420)	82.3 (2090)	83.9 (2130)
Travel speed loaded / unloaded	mph (kph)	10.4 (16.8)   10.4 (16.8)	10.4 (16.8)   10.4 (16.8)	10.3 (16.7)   10.3 (16.7)	10.2 (16.5)   10.2 (16.5)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Mitsubishi / 47.5 (35.4) @ 2250	Mitsubishi / 47.5 (35.4) @ 2250	Mitsubishi / 47.5 (35.4) @ 2250	Mitsubishi / 47.5 (35.4) @ 2250

## STANDARD FEATURES

**2.4 liter balanced engine • EPA compliant • Electronic governor • Fuel system diagnostics • Low LPG warning light • Standard, Triple, Hi-Lo and Quad uprights • Full range of lift heights available • High visibility “silent staging” uprights • Automatic engine shutdown protection • Two-pedal inch-brake system • High capacity cooling system • Auxiliary valve • Routine maintenance points are highly accessible • Isolated operator cell • Clark safety seat • Tilt steering wheel • Clark Information Center, full LED/digital display • Full access clamshell hood • Headlights - overhead guard mounted**



For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at [www.clarkmhc.com](http://www.clarkmhc.com).