

# CMP

IC-PNEUMATIC    LPG/DIESEL  
SINGLE / DUAL DRIVE  
8000 / 9000 / 10,000 lbs.  
(4000 / 4500 / 5000 kg)



## STANDARD SPECIFICATIONS

**40/45/50S**

Manufacturer's Designation		CMP40	CMP45	CMP50S	CMP40	CMP45	CMP50S
Load Capacity / Rated Load	lbs(kg)	8000 (4000)	9000 (4500)	10,000 (5000)	8000 (4000)	9000 (4500)	10,000 (5000)
Height Overhead Guard	in(mm)	88.9 (2257)	88.9 (2257)	88.9 (2257)	88.9 (2257)	88.9 (2257)	88.9 (2257)
Width	in(mm)	61 (1550)	61 (1550)	61 (1550)	61 (1550)	61 (1550)	61 (1550)
Right Angle Stack (add load length and clearance)	in(mm)	133.8 (3400)	135.4 (3440)	136.6 (3470)	133.8 (3400)	135.4 (3440)	136.6 (3470)
Outside Turning Radius	in(mm)	111.4 (2830)	113 (2870)	114.2 (2900)	111.4 (2830)	113 (2870)	114.2 (2900)
Travel speed loaded / unloaded	mph (kph)	11.7 (18.8) / 12.3 (19.9)	11.6 (18.7) / 12.3 (19.9)	11.7 (18.9) / 12.4 (20.0)	13.1 (21.1) / 13.8 (22.3)	13.0 (20.9) / 13.8 (22.3)	13.0 (20.9) / 13.8 (22.3)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Perkins / 1104C.44 82.8(61.5) @ 2200	Perkins / 1104C.44 82.8(61.5) @ 2200	Perkins / 1104C.44 82.8(61.5) @ 2200	GM/Vortec /4300LT 93(69) @ 2400	GM/Vortec /4300LT 93(69) @ 2400	GM/Vortec /4300LT 93(69) @ 2400

### Dual Drive

Manufacturer's Designation		CMP40	CMP45	CMP50S	CMP40	CMP45	CMP50S
Load Capacity / Rated Load	lbs(kg)	8000 (4000)	9000 (4500)	10,000 (5000)	8000 (4000)	9000 (4500)	10,000 (5000)
Height Overhead Guard	in(mm)	87.7 (2227)	87.7 (2227)	87.7 (2227)	87.7 (2227)	87.7 (2227)	87.7 (2227)
Width	in(mm)	74.8 (1900)	74.8 (1900)	74.8 (1900)	74.8 (1900)	74.8 (1900)	74.8 (1900)
Right Angle Stack (add load length and clearance)	in(mm)	134.2 (3410)	134.2 (3410)	134.2 (3410)	134.2 (3410)	134.2 (3410)	134.2 (3410)
Outside Turning Radius	in(mm)	111.4 (2830)	113 (2870)	114.2 (2900)	111.4 (2830)	113 (2870)	114.2 (2900)
Travel speed loaded / unloaded	mph (kph)	11.1 (17.8) / 11.6 (18.7)	11.0 (17.7) / 11.6 (18.7)	10.9 (17.6) / 11.6 (18.7)	12.4 (19.9) / 13.3 (21.4)	12.3 (19.8) / 13.3 (21.4)	12.2 (19.7) / 13.3 (21.4)
Engine / Rated output per SAE J1349	HP(KW) @ rpm	Perkins / 1104C.44 82.8(61.5) @ 2200	Perkins / 1104C.44 82.8(61.5) @ 2200	Perkins / 1104C.44 82.8(61.5) @ 2200	GM/Vortec /4300LT 93(69) @ 2400	GM/Vortec /4300LT 93(69) @ 2400	GM/Vortec /4300LT 93(69) @ 2400

## STANDARD FEATURES

**Sideshifter and internal hosing included • Standard, full free lift Triple Stage and HiLo uprights • Isolated operator cell • Full access clamshell hood • GM 4.3Liter LPG engine • Perkins 1004.4 diesel engine with vertical exhaust • Pre cleaner included • Two-pedal inch-brake system • Enclosed oil-cooled disc brakes • Two-speed electric shift transaxle • Dual Drive on CMP50S available • Hood mounted hydraulic levers • Clark Safety Seat**

For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at [www.clarkmhc.com](http://www.clarkmhc.com).